

# RONDA® Vacuum Cleaner

## Model 550

80.26.2506



RONDA® 550 is a robust wet cleaner with a large suction capacity. Suitable for vacuuming large quantities of water, e.g. for disaster services, emptying of vats, cleaning of basins, draining of cellars and vacuuming of sludge.

The pump transports the water continuously. By less water, the cleaning can also take place without the pump being switched on. The liquid is filtered in the filter bag, and particles >0.5 mm are retained while the rest is pumped out. Easy and effective.

RONDA® 550 is equipped with 2 suction motors, which can be switched on separately to reduce any possible foam creation.

### TECHNICAL DATA

Blow through motor	2x750	W
Voltage	230	V
Power outlet, max.	-	W
<b>Data of the installed motor:</b>		
- Vacuum, max. (per motor)	2000	mmWC
	19,6	kPa
- Air flow, max. (per motor)	50	l/sec.
	180	m³/h.
Noise level (ISO 11201)	<70	dB(A)
Pre-filter	0.34	m²
HEPA-filter	-	m²
Height	920	mm
Width	580	mm
Length/depth	620	mm
Weight without accessories	35	kg
Container coupling	ø 50	mm
Length of supply cable	8	m
Collection capacity, liquid, max.	52	l
Lifting height	7.5	m
Amount of water, pump, max.	187	l/min.
Discharge pipe stub	5/4	Inch

- Continuous vacuuming of liquids
- Submersible pump
- Easy to operate
- Low noise level
- Strong trolley frame
- Also ideal for special solutions
- Retains particles >0.5 mm

# RONDA® Vacuum Cleaner

## Model 550

### STANDARD ACCESSORIES:

<b>40 mm professional's set</b> .....	<b>80.33.4016</b>
1 Plastic hose, ø 38 mm - 4 m .....	84.54.3809
2 Complete tube with bend .....	80.52.2160
3 Crevice nozzle .....	80.34.4000
4 Round brush.....	80.34.4001
5 Wet floor nozzle V-450 .....	84.38.3623

### STANDARD FILTERS:

1 Filter bag with bottom rail .....	84.67.4025
-------------------------------------	------------



### OPTIONAL EXTRAS

- 1 Dust catch. If the machine is used for small amounts of dry dust, a special insert is used to separate the liquid from the dust:  
Easy Clean dust catch .....
  - 5/4" GEKA coupling with connection piece with swivel .....
  - 5/4" GEKA coupling SH .....
  - Hose clamp 25-40mm, inox .....
  - Discharge hose, flat, ø32mm .....
- (Please specify required length in metres)



Last edited: 15/01/20