

RONDA® ENVIRO-VAC

E-VAC 1000 m³/h Open Front 240V



TECHNICAL DATA

110 Volt	3.2 Amps
240 Volt	1.6 Amps
Airflow (BS8520-2)	1195 m ³ /h
Airflow (ISO5801)*	1000 m ³ /h
Noise level:	< 65dB
Filtration Class:	H14
Dimensions:	620mm x 650mm x 590mm
Weight:	27kg
Material:	Polypropylene



*Based on the latest airflow measurement technology there are strong indications that the test method used by BS8520-2 annex A is resulting in an airflow reading which is 30-40% higher than the actual air flow. Both BSI and HSE are looking into this matter. In the meantime we strongly recommend that you base any calculations for your required air extraction on the air flow rates according to ISO 5801

The Enviro-Vac 1000 m³/h Open Front Air Mover is small and compact.

It has been designed and manufactured for the UK and European asbestos removal market.

The Enviro-Vac 1000 m³/h conforms to BS8520 and is available in 110 or 240 Volt.

Constructed from tough polypropylene plastic, with strong seam welding throughout.

Fitted with a H14 HEPA Filter.

A large manometer is fitted to indicate when the filtration system is becoming blocked.

Fitted with Aerofoil Backdraft Flaps, minimising airflow resistance on the outlet.

Lifting handles.

Robust transit cover held in place with 4 locking clips.

Product code: RE102 240V

Product code: RE105 110V

- 110V or 240V options.
- 2-stage filtration system
- H14 HEPA filtration standard to 99.995%
- Transit Cover
- Locking Clips
- Manufactured from tough Polypropylene Plastic
- Fitted with castors

