

RONDA® ENVIRO-VAC

E-VAC 2700 m³/h 3 Stage Product codes:N234 110V



TECHNICAL DATA

| | |
|--------------------|--------------------------|
| 110 Volt | 12.6 Amps |
| 240 Volt | 6.3 Amps |
| Airflow (BS8520-2) | 2700m ³ /h |
| Airflow (ISO5801)* | 1890 ³ /h |
| Noise level: | <84dB |
| Filtration Class: | H14 |
| Dimensions: | H700mm x W590mm x L840mm |
| Weight: | 63kg |
| Material: | Polypropylene |

The Enviro-Vac 2700 m³/h 3 Stage Air Mover is a medium sized machine.

It has been designed and manufactured for the UK and European asbestos removal market.

The Enviro-vac 2700 m³/h conforms to BS8520 and is available in 110 or 240 Volt.

Constructed from tough polypropylene plastic, with strong seam welding throughout.

3-STAGE FILTRATION.

H14 HEPA Filtration to 99.995.

95mm V line panel filter class EN779:2012.

A manometer is fitted to indicate when the filtration system is becoming blocked.

Fitted with aerofolio backdraft flaps, minimising airflow resistance on the outlet.

Lifting handles.

Transit cover held in place with 4 locking clips.

Fitted with lockable castors.



*Based on the latest airflow measurement technology there are strong indications that the test method used by BS8520-2 annex A is resulting in an airflow reading which is 30-40% higher than the actual air flow. Both BSI and HSE are looking into this matter. In the meantime we strongly recommend that you base any calculations for your required air extraction on the air flow rates according to ISO 5801

